



UNITEST Digital Clamp Meter CHB 15 (AC/DC)

Key Functions

- Current voltage and resistance measurement
- Frequency measurement
- Acoustical continuity test
- Min/Max and relative value measurement

General Information

- Automatic selection of the measurement range
- Integrated data hold
- Additional analogue bargraph display
- Clamp opening 23 mm

Special Features

- AC/DC current clamps are also appropriate for the use in automobile workshops, UPSs and solar technology

Technical Data

Display	3 1/4 Digit, LCD, 3999 Digits
Measuring Ranges	
Current AC	0.01...200 A
Tolerance	± (2 % rdg. + 4 Digit)
Current DC	0.01...200 A
Tolerance	± (2 % rdg. + 2 Digit)
Voltage AC	0.1...400 V
Tolerance	± (2 % rdg. + 2 Digit)
Voltage DC	0.1 V...400 V
Tolerance	± (2 % rdg. + 2 Digit)
Input Resistance	10 MΩ
Resistance	0.1...400 Ω
Tolerance	± (2 % rdg. + 2 Digit)
Continuity	R < 40 Ω
Frequency	
Measurement	0.01 Hz...50 kHz
Tolerance	± (1 % rdg. + 2 Digit)
Frequency Range for Current/Voltage AC	40 Hz...1000 Hz
Measurement Category	CAT II, 600 V
Pollution Degree	2
Safety in compl. with	IEC 61010, EN 61010
Clamp Opening	ø 23 mm
Power Supply	2 x 1.5 V, IEC LR 6
Dimensions	183 x 64 x 36mm
Weight	approx. 190 g

**200 A
AC/DC**

**400 V
AC/DC**

0...400 Ω

**Acoustical
Continuity**

**Data
Hold**

**min./max.
Memory**

**Hz
Frequency**

Scope of Supply:

- 1 pc UNITEST Digital Clamp Meter CHB 15
- 2 pc Batteries 1.5 V, IEC LR6
- 2 pc Test Leads (red/black)
- 1 pc Carrying Case
- 1 pc Instruction Manual



Accessories:

Safety-Set
Cat. No. 370003

Order Information:

Description	Cat. No.
UNITEST Digital Clamp Meter CHB 15 Safety-Set	93468 370003